

Application No. 10/607,519
Art Unit 1711
Reply to Office Action of September 28, 2004

AMENDMENTS TO THE SPECIFICATION

Please amend Table 3 on page 29 as follows:

Table 3

| | | Ex. 8 | Ex. 9 | Ex. 10 | Comp. Ex. 7 |
|-----------------------------------|--|---|---------------|---------------|------------------------|
| Polyamide resin composition | Type of PA | PA6T /66 | PA6T /66 | PA6T /66 | PA66 <u>PA6T/66</u> |
| | Amount of PA (part(s) by weight) | 40 | 40 | 40 | 40 |
| | Type and amount (part(s) by weight) of metallic soap | Li-Beh (22 carbon atoms) Mg-Beh (22 carbon atoms) Na-Mon (28 carbon atoms) | 0.2 - - | 0.4 - - | - 0.4 - |
| | Glass fiber (part(s) by weight) | 30 | 30 | 30 | 30 |
| | Flame retardant (part(s) by weight) | 26 | 26 | 26 | 26 |
| | Flame retarding assistant (part(s) by weight) | 4 | 4 | 4 | 4 |
| | Flame retardance | V-0 | V-0 | V-0 | V-0 |
| | HDT (°C) | 296 | 295 | 295 | 295 |
| | Flow length (mm) | 73 | 75 | 76 | 65 |
| | | | | | |